

# SPHERE SERVERS - DATASHEET - TELESPIHERE

Published: 31 March 2011 E&OE Version 1.0

## OVERVIEW

A fully-featured small to medium office telephone system that uses voice-over-internet (VoIP) technologies to deliver a mix of advanced features and low operating costs.

### TeleSphere system:

- Multiple "receptionist" switchboard(s) or none at all
- Handsets/extensions in multiple locations (eg home)
- Call forwarding, to mobile, voicemail or delegated
- Conference rooms - dial-in to join
- Personal voicemail via email and or handset retrieval
- Call recording (on demand)
- Incoming numbers independent of location...
  - your numbers stay with you if/when you move
  - provide local access numbers in foreign locations

### When used alongside an OfficeSphere system:

- User integration
- Intuitive call hunt groups
- one click out-of-office management
- CallerID searches shared contacts
- Call reminders as calendar events

TeleSphere requires compatible VoIP handsets, we recommend the 300 series from Snom but many others are also suitable.

Finally, TeleSphere systems are available for purchase and also on a rental basis with a minimum contract period of just three months. Incoming numbers can be provisioned in minutes and cancelled after one month, making "pop-up" communications a very practical reality for foreign location shoots etc.

## CONTACT US

8-9 Stephen Mews London W1T1AF  
020 7434 3300  
<http://www.sphereservers.com>  
[info@sphereservers.com](mailto:info@sphereservers.com)

## SPECIFICATIONS

Chassis: 1U rackmounting chassis with rails  
Height: 1.75" (44mm)  
Width: 17.2" (437mm)  
Depth: 9.8" (250mm)  
Gross Weight: 10 lbs (4.5kg)

CPU type: 1 Intel 230 Atom  
CPU speed: 1.6 GHz cpu  
RAM: 1GB DDR-2 memory (2GB max)

System disks: 2 x 160GB 7200rpm 2.5 SATA 16Mb cache  
RAID: RAID mirror  
Backplane: SATA 3Gb/s per disk, fixed

Gigabit network: 2 x Realtek gigabit ethernet ports

System software: TeleSphere 1.4.4  
Linux kernel: 2.6.35-2-sphere  
Underlying OS: Debian Linux

Onboard graphics: VGA console output  
Expansion: 2 x USB 2.0 connectors  
Power supplies: 520W psu

## A REAL WORLD EXAMPLE

A small company has some handsets at its office. One of these rings on each incoming call, but if busy/unanswered further phones join the "hunt group" until the call is answered, or routed to voicemail.

Conference calls, transfers, and delegation (proxies) all work as expected. Call recording is available as an option.

Other people are working from home and on location. All calls to and from all handsets are free. All outgoing calls have correct "Caller ID".

The location crew have a local phone number so all calls to them are cheap and simple. This number rings the local handsets first, and falls back to the main office reception if unanswered.

All incoming calls are logged, and tagged against the shared company contacts database. Then the phone bill arrives and it's astonishing!



**Configuration Identity 1** VERSION 7 [Logout](#)

**Operation**  
Home  
Directory

**Setup**  
Preferences  
Speed Dial  
Function Keys  
Identity 1  
Identity 2  
Identity 3  
Identity 4  
Identity 5  
Identity 6  
Identity 7  
Identity 8  
Identity 9  
Identity 10  
Identity 11  
Identity 12  
Action URL Settings  
Advanced  
Trusted Certificates  
Software Update

**Status**  
System Information  
Log  
SIP Trace

**Login SIP NAT RTP**

**Login Information:**

Identity active:  On  Off ?

Displayname: Fun Factory 100 ?

Account: 100 ?

Password: \*\*\*\*\* ?

Registrar: 89.187.67.185 ?

Outbound Proxy: ?

Fallover Identity: None ?

Authentication Username: 100 ?

Mailbox: 100 ?

Ringtone: Ringer 1 ?

Custom Melody URL: <http://thefunfactory.tv/welcome> ?

Display text for idle screen: Ext 100 ?

XML Idle Screen URL: <http://www.sphereservers.net/te> ?

Ring After Delay (sec): ?

Record Missed Calls:  On  Off ?

Record Dialed Calls:  On  Off ?

Record Received Calls:  On  Off ?

[Save](#) [Re-Register](#) [Play Ringer](#)

[Remove Identity](#) [Remove All Identities](#)

